

No. : GZIN2005020858CM Date : May 28, 2020 Page: 1 of 7



CUSTOMER NAME:	FOSHAN TIANGE SCIENCE AND TECHNOLOGY CO., LTD.
ADDRESS:	6TH FLOOR, SUNLEAF BUILDING LIHE ROAD, LISHUI TOWN,
	NANHAI DISTRICT, FOSHAN CITY, GUANGDONG, CHINA

Sample Name	:	Polyester fiber acoustic panel
Product Specification	:	1220×2420×9mm
Manufacturer	:	FOSHAN TIANGE ACOUSTIC DECOR MATERIAL CO., LTD.
Other Information	:	Composition: PET

Above information and sample(s) was/were submitted and confirmed by the client. SGS, however, assumes no responsibility to verify the accuracy, adequacy and completeness of the sample information provided by client.

Date of Receipt	May 14, 2020	
Testing Start Date	May 14, 2020	
Testing End Date	May 28, 2020	
Test result(s)	For further details, please refer to the follow (Unless otherwise stated the results shown the sample(s) tested)	

Signed for SGS-CSTC Standards Technical Services Co., Ltd. GZ Branch Testing Center

Tobby Yang Authorized signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/ent/ferms-and-Conditions.appx and</u>, for electronic format documents, subject to its and Conditions for Electronic Documents at <u>http://www.sgs.com/ent/ferms-and-Conditions.appx and</u>, for electronic format document, attention is drawn to the limitation of liability, indemnification and justiciduon issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is and set and offenders may be prosecuted to the fullest extent of the ise. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of leasting / inspection report accessing score (164, 200, 20155555 f) (86-20) 82075000 www.sgstroup.com.cn. Place / the / company.accessing at their state and black accessing at the score sc



No. : GZIN2005020858CM Date : May 28, 2020 Page: 2 of 7

Test Result Summary

Test(s) Requested	Result(s)	
EN 13501-1:2018 Fire classification of construction products and building	Classification: B-s1, d0	
elements-Part 1: Classification using data from reaction to fire tests		
Cumment		

Summary:

1. For further details, please refer to the following page(s).



Member of the SGS Group (SGS SA)



No. : GZIN2005020858CM Date : May 28, 2020 Page: 3 of 7

TESTS AND RESULTS

Test Conducted:

This test is conducted as per EN 13501-1:2018 Fire classification of construction products and building elements-Part 1: Classification using data from reaction to fire tests. And the test methods as following:

- 1. EN 13823:2010+A1:2014 Reaction to fire tests for building products-Building products excluding floorings exposed to the thermal attack by a single burning item.
- 2. EN ISO 11925-2:2020 Reaction to fire tests-Ignitability of building products subjected to direct impingement of flame-Part 2: Single-flame source test.

Mounting and fixing (For EN 13823:2010+A1:2014):

There is no ventilation cavity behind the specimen.

Test sample is installed on the substrate by screw (test substrates is calcium silicate board meets the requirement of EN13501-1 of Class A2-s1,d0, the density of 900 kg/m³ and thickness of 10mm).

Test Results:

Test method	Parameter	Number of tests	<u>Results</u>
	FIGRA _{0.2MJ} (W/s)		74.2
	FIGRA _{0.4MJ} (W/s)		72.3
	THR _{600s} (MJ)		6.4
	SMOGRA (m²/s²)		2.0
EN 13823:2010+A1:2014	TSP _{600s} (m ²)	3	19.4
	LFS < edge of specimen (Yes/No)		Yes
	Flaming particles or droplets within 600s (Yes/No); Combustion time, if any burning time: (≤10s / >10s)		No
EN ISO 11925-2:2020	<i>F</i> s ≤ 150 mm (Yes/No)	6	Yes
Exposure = 30 s	Ignition of the filter paper	0	No

Remark:

FIGRA-Fire growth rate index used for classification purposes [W/s] For the classes A2 and B, FIGRA_{0.2}MJ For the classes C and D, FIGRA_{0.4}MJ LFS-Lateral flame spread [m] THR_{600s}-Total heat release within 600 s [MJ] SMOGRA-Smoke growth rate [m²/s²] TSP_{600s}-Total smoke production within 600 s [m²]



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/lferms.and-Conditions.for-ad</u>



No. : GZIN2005020858CM Date : May 28, 2020 Page: 4 of 7

Classification and direct field of application:

This classification has been carried out in accordance with EN 13501-1:2018.

Classification:

Fire behaviour		Smoke p	roduction		Flaming	droplets
В	_	s	1	,	d	0

Remark:

The classes with their corresponding fire performance are given in Table 1. Reaction to fire classification is based on the 7-step scale of A1 to F, where A1 is good and F is bad

Statement:

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

Warning:

This classification report does not represent type approval or certification of the product. The test laboratory has, therefore, play no part in sampling the product for the test, although it holds appropriate references to the manufacturer's factory production control that is aimed to be relevant to the samples tested and that will provide for their traceability.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.gs.com/en/Terms.and-Conditions.asp.cand, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.gs.com/en/Terms.and-Conditions.T

188 Kachu Road, Scientech Park, Economic & Technical Development District, Guangzhou, China. 510663 t (86-20) 82155555 f (86-20) 82075080 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075080 e sgs.china@sgs.com



No. : GZIN2005020858CM Date : May 28, 2020 Page: 5 of 7

Table 1 — Classes of reaction to fire performance for construction products excluding floorings and linear pipe thermal insulation products.

Class	Test method(s)		Classification criteria	Additional classification
	EN ISO 1182 a and		△ $T \le 30^{\circ}$ C, and △ $m \le 50^{\circ}$, and $t_{f} = 0$ (i.e. no sustained flaming)	-
A1 EN ISO 1716		6	PCS≤2.0MJ/kg ^a and PCS≤2.0MJ/kg ^{bc} and PCS≤1.4MJ/m ^{2d} and PCS≤2.0MJ/kg ^e	-
	EN ISO 1182 ª or		⊿ <i>T</i> ≤50°C, and ⊿ <i>m</i> ≤50%, and t _f ≤20 s	-
A2	EN ISO 1716	and	PCS≤3.0MJ/kg ^a and PCS≤4.0MJ/m ² ^b and PCS≤4.0MJ/m ² ^d and PCS≤3.0MJ/kg ^e and	-
	EN 13823		<i>FIGRA</i> ≤120W/s and <i>LFS</i> <edge and<br="" of="" specimen=""><i>THR</i>_{600s}≤7.5MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
В	EN 13823 and		FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR600s≤7.5MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
	EN ISO 11925-2 ¹ Exposure =30s		Fs≤150mm within 60 s	
С	EN 13823 and EN ISO 11925-2 [†] Exposure=30s		FIGRA≤250W/s and LFS <edge and<br="" of="" specimen="">THR600s≤15MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
			Fs≤150mm within 60 s	
	EN 13823	and	FIGRA≤750W/s	Smoke production fand
D	EN ISO 11925-2 [†] Exposure=30s		Fs≤150mm within 60 s	Smoke production ^f and Flaming droplets/particles ^g
E	EN ISO 11925-2 ⁱ Exposure =15s		Fs≤150mm within 20 s	flaming droplets/particles h
F	EN ISO 11925-2 ⁱ Exposure =15s		Fs>150mm within 20 s	-



nless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed verteal, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, ubject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, ubject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for why holder of this document is twised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of ansaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced kcept in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the suits shown in this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only. **Hatton:** The check the authenticity of testing / imspection report. Scrifticate, please contact us at telephone:(86-755) 8307 **H43, or email:** CR.Doccheck@sgs.com

1445、00 Final: 01:000C016482395-000 18/8/kn/ka3, Sciench Park, Economic Bechnical Development District, Guangzhou, China. 510663 tl (86-20) 82155555 fl (86-20) 82075080 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学城科珠路198号 邮编: 510663 tl (86-20) 82155555 fl (86-20) 82075080 e sgs.china@sgs.com



No. : GZIN2005020858CM Date : May 28, 2020 Page: 6 of 7

- ^a For homogeneous products and substantial components of non-homogeneous products.
- ^b For any external non-substantial component of non-homogeneous products.
- ^c Alternatively, any external non-substantial component having a PCS \leq 2,0 MJ/m², provided that the product satisfies the following criteria of EN 13823: FIGRA \leq 20 W/s, and LFS < edge of specimen, and THR_{600s} \leq 4,0 MJ, and s1, and d0.
- ^d For any internal non-substantial component of non-homogeneous products.
- ^e For the product as a whole.
- ^f In the last phase of the development of the test procedure, modifications of the smoke measurement system have been introduced, the effect of which needs further investigation. This may result in a modification of the limit values and/or parameters for the evaluation of the smoke production.
- s1 = SMOGRA \leq 30m²/s² and TSP_{600s} \leq 50m² ; s2 = SMOGRA \leq 180m²/s² and TSP_{600s} \leq 200m²; s3 = not s1 or s2
- ^g d0 = No flaming droplets/ particles in EN 13823 within 600 s;
- d1 = no flaming droplets/ particles persisting longer than 10 s in EN 13823 within 600 s; d2 = not d0 or d1.
- Ignition of the paper in EN ISO 11925-2 results in a d2 classification.
- ^h Pass = no ignition of the paper (no classification);
- Fail = ignition of the paper (d2 classification).
- ⁱ Under conditions of surface flame attack and, if appropriate to the end-use application of the product, edge flame attack.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/IFerms.and.Conditions.app</u> and. Conditions for Electronic Documents at <u>http://www.sgs.com/en/IFerms.and.Conditions.app</u> and. Attention is drawn to the limitation or liability, indemnification and <u>juris defined therein</u>. Any holder of hils document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of transaction from exercicing all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention is check the authenticity of testing / inspection report & context the suthenticity of testing / inspection report 67.80 8307 1484, or email: CN.Doccheck@sgs.com.

188 Kezhu Road, Scientech Park, Economic & Technical Development District, Guangzhou, China. 510663 t (86-20) 82155555 f (86-20) 82075080 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075080 e sgs.china@sgs.com



No. : GZIN2005020858CM Date : May 28, 2020 Page: 7 of 7

SAMPLE INFORMATION AND PICTURES

Thickness of the test specim en: Density of the test specimen:

About 10 mm About 2.30 kg/m²



Before Test (EN 13823)



After Test (EN 13823)

Appendix information: The above test was carried out by SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch.

******** End of report*******



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overteaf, available on request or accessible at <u>http://www.sgs.com/en/lferms.and-Conditions.app</u> and. Conditions format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/lferms.and-Conditions.Terms.and-Condition</u>

Member of the SGS Group (SGS SA)